

# APPLICATION UNDER UNITED STATES PATENT LAWS

Atty. Dkt. No. • 008312-0305778 \_\_\_\_\_

Invention: INFORMATION RECORDING AND PLAYBACK APPARATUS

Inventor (s): Kazuyo HASHIYA  
Masahiro ITO

Address communications to the  
correspondence address  
associated with our Customer N

00909

Pillsbury Winthrop LLP

This is a:

- ☐ Provisional Application
- ☒ Regular Utility Application
- ☐ Continuing Application
  - ☐ The contents of the parent are incorporated by reference
- ☐ PCT National Phase Application
- ☐ Design Application
- ☐ Reissue Application
- ☐ Plant Application
- ☐ Substitute Specification
  - Sub. Spec. Filed \_\_\_\_\_
  - in App. No. \_\_\_\_\_ / \_\_\_\_\_
- ☐ Marked up Specification re
  - Sub. Spec. filed \_\_\_\_\_
  - In App. No. \_\_\_\_\_ / \_\_\_\_\_

## SPECIFICATION

TITLE OF THE INVENTION  
INFORMATION RECORDING AND PLAYBACK APPARATUS

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is based upon and claims the  
5 benefit of priority from the prior Japanese Patent  
Application No. 2002-348713, filed November 29, 2002,  
the entire contents of which are incorporated herein by  
reference.

BACKGROUND OF THE INVENTION

10 1. Field of the Invention

This invention relates to an information recording  
and playback apparatus which can record and play back  
information. In particular, it relates to an  
information recording and playback apparatus, wherein  
15 start and end of information recording can be set from  
outside.

2. Description of the Related Art

In information recording and playback apparatuses  
which play back or record an information medium storing  
20 video data, such as image information, and control  
information, the following are set with the apparatus  
main body or an accompanying remote control device:  
recording start date and time/recording end date and  
time; recording source; and recording rate and  
25 recording system (sound recording system), etc  
(hereinafter simply referred to as "recording  
programming"). Thereby, a desired (preselected)

recording source is recorded on the preselected date and time, with the predetermined recording rate and recording system.

Nowadays, information recording and playback apparatuses are in practical use, which can reduce an amount of the information to be inputted with the apparatus main body or a remote control device. In such apparatuses, a recording programming code called "G code" is inputted instead of predetermined data determined by broadcasters, such as recording (broadcasting) start date and time/recording (broadcasting) end date and time and recording source, in the data used for recording programming.

Further, Jpn. Pat. Appln. KOKAI Publication No. 8-306097 discloses a remote control device, which has an extension setting section and can extend the recording end time by 15 minutes for each operation of the extension setting section, in such a case where the broadcasting time of the program being recorded has been extended and its end time has been changed, or it has been found before start of recording that wrong recording end time was inputted.

However, these techniques have a problem that the user cannot change the input recording programming information or add a new recording programming, if the user cannot return from a position distant from the information recording and playback apparatus, or if the

user is out, after recording programming.

#### BRIEF SUMMARY OF THE INVENTION

According to an aspect of the present invention, there is provided an information recording and playback apparatus comprising: an information recording and playback section which records information on a recording medium, and plays back prestored information from a recording medium; a timer section which operates the information recording and playback section at a predetermined operation starting time, and stops the information recording and playback section at a predetermined operation ending time; a memory section which holds operation information of the timer section; a communications control section which inputs and sets the operation starting time and the operation ending time to the timer section from outside; a main-power internally-controllable switch, which always energizes to the timer section, and selectively energizes to the information recording and playback section and the communications control section by external operation or management of the timer section; a radio clock section which receives a standard value used for time correction of the timer section from the outside; and a main control section which controls operations of the information recording and playback section, the timer section, the main-power internally-controllable switch and the radio clock receiving section, with reference

to the operation starting time and the operation ending time supplied through the communications control section.

According to another aspect of the present invention, there is provided an information recording and playback apparatus which records and plays back video data, the apparatus comprising: means for receiving a recording programming mail including recording programming contents from outside in a predetermined condition; and means for entering a recording programming in accordance with a recording programming contents in a programming mail acquiring by the receiving means.

According to still another aspect of the present invention, there is provided a method entering and acquiring a recording programming contents from outside with a recording programming mail using an information recording and playback apparatus comprising: receiving a recording programming mail including recording programming contents from outside; and entering a recording programming in accordance with a recording programming contents in a programming mail acquiring by a receiving means.

#### BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWING

The accompanying drawings, which are incorporated in and constitute a part of the specification, illustrate embodiments of the invention, and together

with the general description given above and the detailed description of the embodiments given below, serve to explain the principles of the invention.

FIG. 1 is a schematic block diagram showing an example of a recording and playback apparatus to which an embodiment of the present invention is applicable;

FIG. 2 is a schematic diagram showing an example of arrival of mails on the recording and playback apparatus, sending of mails from the recording and playback apparatus, and transmission and reception of mails between a mail server and a portable terminal;

FIG. 3 is a schematic diagram illustrating an example of a screen of setting a mail recording programming function;

FIG. 4 is a flow chart illustrating a method of receiving a mail when a main power is on;

FIG. 5 is a flow chart illustrating another method of receiving a mail when a main power is on;

FIG. 6 is a flow chart illustrating a method of receiving a mail when a main power is off;

FIG. 7 is a flow chart illustrating a method of receiving a mail when a programmed recording has been completed;

FIG. 8 is a flow chart illustrating a method of receiving a mail when a programmed recording has been completed, if the apparatus is set to turn off the main power after the operation has been completed;

FIG. 9 is a flow chart illustrating an example of receiving a mail, by turning on the main power by MPU mail starting processing when the main power is off; and

5           FIG. 10 is a flow chart illustrating another example of receiving a mail, by turning on the main power by MPU mail starting processing when the main power is off.

#### DETAILED DESCRIPTION OF THE INVENTION

10           An embodiment of the present invention is being explained in detail with reference to drawings.

          A recording and playback apparatus 1 shown in FIG. 1 comprises an information recording and playback section 111 which can record input information in a  
15           predetermined recording medium and play back information stored already in a recording medium in response to a playback operation, and a microcomputer (MPU, that is, a main control unit) 101 which controls recording in, and playback from, the information  
20           recording and playback section 11, and operations of sections explained below.

          The information recording and playback section 111 comprises a disk drive unit 113 which can record information in, and play back information from, a disk  
25           D manufactured in compliant with the DVD (Digital Versatile Disk) standard, and a temporary recording section 115 functioning as a buffer memory, which can

temporarily hold a certain amount of data to be recorded in, or data reproduced from, a disk D set in the disk drive unit 113.

5       In the case where, for example, all the available memory of the disk D has been filled during recording, the temporary recording section 115 temporarily holds information to be recorded, until the disk D has been changed to a disk having an available memory area. In addition to the disk drive unit 113, a hard disk drive  
10       HDD may be provided, which is suitable for recording and retrieval (playback) of massive information.

      The information recording and playback section 111 is connected with an encoder 121 which encodes input information into a form recordable by the information  
15       recording and playback section 111, and a decoder 131 which decodes information outputted from the information recording and playback section 111 into a form displayable by an output device described below.

      The encoder 121 is connected with an AV (Audio  
20       Video) input section 123 to which recording information, being image information or the like, can be inputted from the outside, and a tuner section 125 which receives images and sounds distributed from information distributors, such as broadcasters.

25       The decoder 131 is connected with an AV (Audio Video) output section 133 which supplies playback information decoded (by the decoder 131) to an output



device, typified by a playback equipment (television) and a monitor.

The MPU 101 is also connected with a timer microcomputer section 141. The timer microcomputer section 141 receives an input signal from the recording and playback apparatus 1, or from an accompanying remote control terminal (remote control device) R. The input signal includes recording programming information such as recording (broadcasting) start date and time/recording (broadcasting) end date and time; recording source; and recording rate and recording system (sound recording system), etc (hereinafter simply referred to as "recording programming").

Further, the timer microcomputer section 141 is connected with a timer circuit (clock unit) 143 which manages time used for managing operation of the recording and playback apparatus 1, a radio clock receiving section 145 which receives standard time information from the outside, a switch control section 147 which turns on a main switch MSW, connected to a commercial power source, in response to the user's request, and a user operation input section 149 which receives an operation request (instructions) from the user.

The MPU 101 is also connected with a display section 151 which displays information inputted to the timer microcomputer section 141 or an operation state

of the apparatus 1, a communications control section 103 which receives a recording programming from the outside and informs a designated destination whether the recording programming is acceptable or not, through  
5 a network NT, and a memory 105 which stores recording programming information and the like. Further, the communications control section 103 is provided with a memory (not shown) containing browser software (application software for enabling finding and browsing  
10 of information in a network) widely used in the network NT, a microcomputer (control unit, not shown), and a dialer which secures communications for transmitting mails to the outside under predetermined conditions.

The MPU 101 controls, recording, copying and  
15 deleting with respect to the disk D, and controls changes of operation of the recording and playback apparatus inputted to the timer microcomputer section 141 through the user operation input section 149, and display to the user with the display section 151,  
20 in accordance with a control program stored in the memory 105.

The main switch MSW keeps a secondary circuit (not shown), which operates the MPU 101 and the timer microcomputer section 141, always turned on, in the  
25 state being connected to the commercial power source. The main switch is a main-power internally-controllable type switch, which can start the main power inside the

apparatus by operation of the switch by the user or by control of the timer microcomputer section 141.

5       The timer microcomputer section 141 manages the recording programming information set by the user, while monitoring the timer circuit (clock unit) 143, and instructs the MPU 101 to start recording when the programmed recording start time has come, and instruct the MPU 101 to end the recording when the programmed recording end time has come. Further, the timer  
10       microcomputer section 141 monitors time taken until a time-calibrating timing for calibrating the clock unit (timer circuit) 143, and turns on the main power of the main switch MSW a predetermined time before the time-calibrating timing and sets the radio time  
15       receiving section 145 to a standby state.

      The switch control section 147 starts (turns on) the main switch MSW when it receives instructions from the timer microcomputer section 141 to turn on the main switch MSW, and keeps the main switch MSW on until it  
20       is instructed to turn off the switch.

      The user operation input section 149 receives an operation request from the user, such as change of the operation of the recording and playback apparatus and reception of the recording programming information.  
25       The user operation input section 149 comprises a data receiving section which receives a control signal from the remote control device (remote control terminal) R,

and a control signal input section (not shown) which  
outputs a control signal to the timer microcomputer  
section 141 in response to an instruction directly  
inputted by the user with an operation panel (not  
5 shown) of the main body of the apparatus 1.

The following is an explanation of an example of  
operation in which recording programming information is  
inputted from a portable terminal 201, in the state  
where the main power of the recording and playback  
10 apparatus 1, that is, the main switch MSW is on by the  
user, with reference to FIG. 2.

As shown in FIG. 2, an existing communication  
apparatus (portable terminal) 201, represented by  
personal computers PC and cellular phones CP, transmits  
15 an E-mail (hereinafter simply referred to as "mail") M  
containing recording programming information from the  
user to a mail server (commercial communications  
control unit for network) 299. The recording and  
playback apparatus 1 distinguishes whether the body of  
20 the mail received from the mail server 299 contains a  
specific character string. If the mail contains the  
specific character string, the recording and playback  
apparatus 1 judges the character string to be  
programming information, and set a recording  
25 programming in the recording and the playback apparatus  
1 itself. The mail server 299 holds mails M  
transmitted from the portable terminal 201, such that

the communications control section 103 of the recording and playback apparatus 1 designated by the user can access the mails through the network NT shown in FIG. 1. Further, the recording programming information inputted from the portable terminal 201 is transmitted as a code string expressed in a predetermined form in the body of the mail.

In the state where the recording and playback apparatus 1 is powered, the recording and playback apparatus 1 can access the mail server 299 at time intervals set by the user.

FIG. 3 shows an example of a display for setting a mail recording programming function. The item "POP 3 access intervals" on display indicates intervals of accesses to the mail server 299. In this example, it is set to "120 minutes". Thus, the recording and playback apparatus 1 accesses the mail server 299 and checks whether at least one new mail M have arrived, every 120 minutes from the point of time when the main switch MSW of the recording and playback apparatus 1 has been turned on.

FIG. 4 is a schematic diagram showing an operation of the recording and playback apparatus, which is performed each access time.

When the time managed by the clock unit 143 has reached an access time, the MPU 101 checks the operation state of the recording and playback apparatus

1, and obtains from the memory 105 the number of programs which have already been set to be recorded, to judge whether a new recording programming is possible or not (S1). For example, if the number of the set  
5 programs is equal to the maximum number of recordable programs, no more recording programming cannot be entered, and thus the new recording programming is not accepted. Further, if a recording programming information table in the memory 105 cannot be updated  
10 since a programmed recording is being performed, etc., a recording programming cannot be set (S1-No).

If a recording programming is impossible, the apparatus sends a mail notifying that a recording programming is impossible (S2). Then, a POP3 access-  
15 interval-measuring timer is started (S3) for receiving mail M next time, and an access (mail receive) to the mail server 299 ends.

If a recording programming is possible (S1-Yes), the apparatus acquires the mail M from the mail server  
20 299 (S4).

Then, to judge whether the mail M is a recording programming mail, it is checked whether the received mail M includes a line of character string beginning with a character string "open". If the mail M includes  
25 the character string "open", the apparatus judges the mail M to be a recording programming mail.

Specifically, if the apparatus receives a mail M

having a description "open, pass, 20020830, 1000, 1200,  
4, S, A", the character string "open" indicates that  
the mail is a recording programming mail, and it is  
regarded that the string "pass" indicates a password,  
5 the string "20020830" indicates the recording date  
being August 30, 2002, the string "1000, 1200"  
indicates that the recording is started at 10:00 and  
ended at 12:00, and the string "4, S, A" indicates that  
the channel number 4 is designated as the recording  
10 source, the image quality SP (standard recording mode)  
and the sound quality DD1 (Dolby Digital 1) are  
designated as the recording rate.

Since information defined by a predetermined  
decimal digits, for example 8-digit number may be a  
15 recording programming code called "G-code" in JAPAN,  
and called "VCR Plus+" in USA (United States of  
America) or in UK (United Kingdom) and called "SHOW  
VIEW" in French Republic and the Federal Republic of  
Germany, it is judged whether the number string  
20 following the string "pass" is a recording programming  
code or not (S5).

If the number string is a recording programming  
code, first four digits thereof indicate a number which  
does not correspond to a year of the Christian Era, and  
25 thereby the string is judged a recording programming  
code (S5-Yes). If it is a recording programming code,  
the recording start date and time, the recording end

time, and channel number (the user does not need to select the recording source, in the case of using a recording programming code) is obtained therefrom. Therefore, the recording rate is then read (S6), and they are additionally entered in the recording programming information table in the memory 105 (S7).

If the number string is not a recording programming code (S5-No), the recording start date and time, the recording end time, recording source and recording rate, which are necessary for a recording programming, are read from the mail M, and additionally entered in the recording programming information table of the memory 105 (S7).

Then, it is judged whether mail receiving time is ended or not (S8). If it is not ended and mail reception is continuable (S8-No), step S1 (judging whether a recording programming is possible) to step S8 are repeated. Judgment as to whether it is possible to continue mail receive is performed, if a certain time has passed since start of mail receive or the apparatus has received a user's request of canceling mail receive.

If mail receive has ended (S8-Yes), the apparatus starts the POP3 access-interval-measuring timer for receiving mails next time, and ends the operation (S3).

FIG. 5 shows a modification of the operation of the recording and playback apparatus, explained above



with reference to FIG. 4. FIG. 5 is different from  
FIG. 4 in that the order of receiving mails from the  
mail server and judging whether a recording programming  
is possible or not is reversed, and in the processing  
5 performed when recording programming is impossible.  
The other parts of FIG. 5 are the same as those of  
FIG. 4.

In FIG. 5, when the managed time has reached an  
access time, first the apparatus accesses the mail  
10 server, and acquires a recording programming mail  
therefrom (S11).

After acquiring the recording programming mail,  
the apparatus judges whether a recording programming is  
possible or not (S12). If a recording programming is  
15 possible (S12-Yes), the recording programming is  
entered in the same procedure as in steps S5 to S8  
shown in FIG. 4. Specifically, the apparatus judges  
whether the acquired mail includes a recording  
programming code or not (S14). If it includes a  
20 recording programming code (S14-Yes), the recording  
rate is then read (S15), and they are additionally  
entered in the recording programming information table  
in the memory 105 (S16). Further, if it does not  
include a recording programming code (S14-No), the  
25 apparatus reads the recording start date and time, the  
recording end time, the recording source and the  
recording rate, which are necessary for recording

programming, from the mail M, and they are additionally entered in the recording programming information table in the memory 105 (S16).

5        If the recording programming is impossible although the apparatus has acquired the programming mail (S12-No), the apparatus sends a mail notifying that the recording programming by mail was not accepted (S13).

10        When the recording programming has been entered in the recording programming information table, the apparatus checks whether mail receive has ended or not (S17). If it has ended, the apparatus starts the POP3 access-interval-measuring timer for next mail receive, and ends the operation (S18).

15        Next, operation of receiving recording programming information by using a mail in the state where the main power of the recording and playback apparatus is off will now be described with reference to FIG. 6.

20        In the recording and playback apparatus 1, when the time clocked by the timer circuit 143 has approached a preset time, the main switch MSW is started by control by the switch control section 147 (in response to instructions from the timer micro-computer section 141). Thereby, an internal power of  
25        the apparatus 1 is turned on to adjust or correct the time.

      Since the internal power has been turned on to

adjust or correct the time, a recording programming by mail is performed in the same procedure as explained above with reference to FIG. 4 or 5. Although FIG. 6 shows an example including the procedure of FIG. 4, the same effect is obtained in the case of including the procedure of FIG. 5.

Specifically, after a recording programming has been completed in accordance with the recording circuit 143 is calibrated in accordance with the standard time received by the radio clock receiving section 145 (S23).

FIG. 7 shows an example of control which enables a recording programming by mail, in the case where recording programming is impossible although a programming mail has been received, since the recording and playback apparatus is recording a program.

As explained above, the recording programming information table in the memory 105 cannot be updated, while the apparatus is performing a recording in accordance with a preset recording programming. Therefore, even if the apparatus has received a mail M from the mail server 299, a recording programming cannot be entered.

Therefore, if the apparatus is performing a recording in accordance with the preset recording programming, when the recording end time of the programmed recording has come and the timer

microcomputer section 141 sends a notice to end the recording, the apparatus performs recording ending processing (S31). Thereafter, the apparatus receives mail M in the same procedure as described above with reference to FIG. 4 or 5, and enters (sets) recording programming contents of the mail in the memory 105. Thereby, a new recording programming instructed by the mail M is set. Although FIG. 7 shows an example including the procedure of FIG. 4, the same effect is obtained if it includes the procedure of FIG. 5 instead.

FIG. 8 is a schematic diagram showing a modification of the recording programming explained with reference to FIG. 7.

If the apparatus is performing a recording in accordance with the preset recording programming, when the recording end time of the programmed recording has come and the timer microcomputer section 141 sends a notice to end the recording, the apparatus ends the recording (S31). Thereafter, in many cases, the main power for the recording and playback apparatus 1 is turned off (the main switch MSW is turned off), until the recording start time of the next programmed recording comes. This state is the same as the procedure ending explained with reference to FIG. 7.

However, to receive a mail M and enter a recording programming, it is required that the main power of

the apparatus is on. Therefore, when the previous programmed recording has been completed, the apparatus judges whether the apparatus has been set to turn off the power after a programmed recording has been completed (S41). If it is set to turn off the power after a programmed recording (S41-Yes), the apparatus instructs the switch control section 147 to extend the time that elapses before the main switch MSW is turned off (S42).

Then, the apparatus receives the mail M in the same procedure as explained above with reference to FIG. 4 or 5, and enters (sets) recording programming contents of the mail in the memory 105. Thereby, a new recording programming instructed by the mail M is set.

When the recording programming has been completed in accordance with the recording programming information, the MPU 101 instructs the switch control section 147 to turn off the main switch MSW, and the main power is turned off (S43).

As described above, in the recording programming operations shown in FIGS. 7 and 8, it is possible to set whether the main power is to be turned off or kept turned on after programmed recording, copy or delete of an image, and disk format, etc.

FIG. 9 is a schematic diagram showing another example of the recording programming operation by mail to the recording and playback apparatus, explained with

reference to FIGS. 4 to 8.

When the mail server 299 has notified the MPU 101 of the recording and playback apparatus 1 that a new mail M from a cellular phone 201 or the like has  
5 arrived, even if the main switch MSW is off, the main switch MSW is turned on by the switch control section 147 to receive the programming mail, and thereby the apparatus 1 is started (S51). In such a case, to receive the mail, only the function of receiving mails  
10 and the function of performing recording programming may be started, unlike normal turn-on of the power (MPU mail starting processing).

Specifically, in the normal start of the apparatus, the apparatus performs routines, such as  
15 recognition of media (disk medium) inserted in the disk drive unit 113 and initialization of the encoder 121 and the decoder 131. In performing recording programming by mail, functions other than the function of receiving mails and the function of performing  
20 recording programming may be left unstated.

Then, the apparatus receives mail M in the same procedure as described above with reference to FIG. 4 or 5, and enters (sets) recording programming contents of the mail in the memory 105. Thereby, a new  
25 recording programming instructed by the mail M is set.

When the programming in accordance with the recording programming information has been completed,

the MPU 101 instructs the switch control section 147 to turn off the main switch MSW, and the main power is turned off (S43).

FIG. 10 is a schematic diagram showing another example of the recording programming operation by mail to the recording and playback apparatus, explained with reference to FIG. 9.

As shown in FIG. 10, from the state in which the main power of the recording and playback apparatus 1 is off, the main power of the apparatus 1 is turned on by turning on the main switch MSW by user's operation, and thereby normal starting processing (MPU starting processing) is performed (S61).

In MPU starting processing, starting the encoder 121 and the decoder 131, resetting the disk drive unit 113, and recognizing media and the like are performed in accordance with a predetermined initializing sequence (S62).

After the MPU starting processing, before enabling reception of control signals corresponding to key operation by the user, the apparatus receives mail M in the same procedure as described above with reference to FIG. 4 or 5, and enters (sets) recording programming contents of the mail in the memory 105. Thereby, a new recording programming instructed by the mail M is set.

As described above, according to the present invention, it is possible to acquire a recording

programming mail containing recording conditions, even under various operation conditions of the apparatus, and thus recording programming by mail can be securely entered. For example, a recording programming mail is  
5 acquired: at regular time intervals while the main power of the recording and playback apparatus is on; at the time of time-adjusting operation if the main power is off; when completion of operation, such as recording in accordance with the recording programming stored in  
10 the memory, during which the recording data cannot be updated; when a new recording programming mail has been received during waiting state (the main power is off); at regular time intervals when the apparatus is on standby with the main power off; and at the time of  
15 starting by turning on the main power.

Further, it is possible to set a recording programming by E-mail even if the main power is not kept turned on, by acquiring a recording programming mail when the internal power of the recording and  
20 playback apparatus is turned on for time adjustment, in the stand-by state with the main power off.

Furthermore, it is possible to set a recording programming by E-mail even if a recording programming was not accepted by a periodical processing, by  
25 acquiring the recording programming mail after the operation during which recording programming is impossible.



It is also possible to set a recording programming by E-mail even in the case where the power is off before operation of periodical processing, by acquiring a recording programming mail at the time of completion of an operation, at completion of which the apparatus is set to be turned off.

It is also possible to set a recording programming by E-mail even if the main power is not on, by turning on the power if the mail server has received a new mail when the main power of the recording and playback apparatus is off, and acquiring the recording programming mail.

It is also possible to set a recording programming by E-mail even if the main power is not on, by turning on the internal power of recording and playback apparatus at regular time intervals when the main power is off, and acquiring a recording programming mail.

It is also possible to set a recording programming by E-mail, by acquiring a recording programming mail when the main power of the recording and playback apparatus is turned on.

Therefore, it is possible to set recording start time and recording end time of information even under conditions in which recording programming by using the apparatus main body or the remote control device is difficult, and it is possible to prevent failing in recording due to the user's being in a position distant

from the apparatus.

Additional advantages and modifications will readily occur to those skilled in the art. Therefore, the invention in its broader aspects is not limited to  
5 the specific details and representative embodiments shown and described herein. Accordingly, various modifications may be made without departing from the spirit or scope of the general inventive concept as defined by the appended claims and their equivalents.